

Package: newIMVC (via r-universe)

September 15, 2024

Type Package

Title A Robust Integrated Mean Variance Correlation

Version 0.1.0

Description Measure the dependence structure between two random variables with IMVC and extend IMVC to hypothesis test, feature screening and FDR control.

License MIT + file LICENSE

Encoding UTF-8

Imports splines, quantreg, expm, CompQuadForm, GGMridge, limma

RoxygenNote 7.2.3

Repository <https://scottpanhan.r-universe.dev>

RemoteUrl <https://github.com/scottpanhan/newimvc>

RemoteRef HEAD

RemoteSha 93e66fb6e8c112063f6f7543234ee0bbdf385329

Contents

IMVC	1
IMVCFDR	2
IMVCS	3
IMVCT	3

Index	4
--------------	----------

IMVC *Integrated Mean Variance Correlation*

Description

This function is used to calculate the integrated mean variance correlation between two vectors

Usage

```
IMVC(y, x, K, NN = 3, type)
```

Arguments

y	is a numeric vector
x	is a numeric vector
K	is the number of quantile levels
NN	is the number of B spline basis, default is 3
type	is an indicator for measuring linear or nonlinear correlation, "linear" represents linear correlation and "nonlinear" represents linear or nonlinear correlation using B splines

IMVCFDR

Integrated Mean Variance Correlation Based FDR Control

Description

This function is used for FDR control with integrated mean variance correlation

Usage

```
IMVCFDR(y, x, K, NN = 3, numboot, timeboot, true_signal, null_method, alpha)
```

Arguments

y	is the response vector
x	is the covariate matrix
K	is the number of quantile levels
NN	is the number of B spline basis, default is 3
numboot	is the size of bootstrap samples
timeboot	is the number of bootstrap times for computing standard deviation of the IMVC
true_signal	is the true active set
null_method	is the estimation method for proportion of true null hypotheses. Choices are "lfdr", "mean", "hist" or "convest"
alpha	is the nominal FDR level

Value

A list of FDP, power and selected variables

 IMVCS

Integrated Mean Variance Correlation Based Screening

Description

This function is used to select important features using integrated mean variance correlation

Usage

```
IMVCS(y, x, K, d, NN = 3, type)
```

Arguments

y	is the response vector
x	is the covariate matrix
K	is the number of quantile levels
d	is the size of selected variables
NN	is the number of B spline basis, default is 3
type	is an indicator for measuring linear or nonlinear correlation, "linear" represents linear correlation and "nonlinear" represents linear or nonlinear correlation using B splines

 IMVCT

Integrated Mean Variance Correlation Based Hypothesis Test

Description

This function is used to test significance of linear or nonlinear correlation using integrated mean variance correlation

Usage

```
IMVCT(x, y, K, num_per, NN = 3, type)
```

Arguments

x	is the univariate covariate vector
y	is the response vector
K	is the number of quantile levels
num_per	is the number of permutation times
NN	is the number of B spline basis, default is 3
type	is an indicator for measuring linear or nonlinear correlation, "linear" represents linear correlation and "nonlinear" represents linear or nonlinear correlation using B splines

Index

IMVC, 1
IMVCFDR, 2
IMVCS, 3
IMVCT, 3